

# SR-23

## ROCKER SWITCH SR-23 SERIES



SR-23A



SR-23A



SR-23C

### SPECIFICATIONS



3(1)A	250VAC	T105	
10(4)A	250VAC	T105	5E4
10(6)A	250VAC	T105	
16(6)A	250VAC	T105	
3A	250VAC	T105	
6A	125VAC		
10A	250VAC	T105	
16A	125VAC		
1/2HP	250VAC	T105	
1/4HP	125VAC		





### FEATURES

- Usage: General purpose  
用途：通用
- Single Pole  
單極
- With ON-OFF-ON function / America pannel opening  
具有ON-OFF-ON功能 / 美洲面板開口
- Temperature Rating: -10°C~105°C  
額定溫度：-10°C~105°C
- Flammability Rating: UL94V-2 / Optional UL94V-0  
可燃性等級：UL94V-2 / 可選 UL94V-0

### ORDER INFORMATION

A	L	T	BK	BK	1	1	0	0	
FUNCTION	CURRENT	TERMINAL TYPE	BASE COLOR	BUTTON COLOR	BASE TYPE	BUTTON TYPE	PRINTING	COLOR OF PRINTING	INTERNAL USE ONLY
A ON-OFF	L 16(6)A 250VAC	T	BK Black	BK Black	1	1	0 NONE	0 None	
B ON-ON	10(4)A 250VAC 5E4		WT White	WT White	2		1	1 White	
C ON-OFF-ON	16A 125VAC		GE Grey	GE Grey			2	2 Black	
	1/2HP 250VAC		RE Red	RE Red			3	3 Red	
	1/4HP 125VAC		GR Green	GR Green			4	4 Blue	
	S 3A 250VAC		BL Blue	BL Blue			5	5 Yellow	
	6A 125VAC		OR Amber	OR Amber			6		
	3(1)A 250VAC		YE Yellow	YE Yellow			7		
							8		
							9		
							A		

Remark: Without tooling for metal parts of funtion B



### SUGGESTED PANEL HOLE SIZE

Panel thickness	x
0.8 ~ 2.0	28.8

