

SR-08

ROCKER SWITCH SR-08 SERIES

ROCKER SWITCH



ROTARY SWITCH

PUSH SWITCH

MICRO SWITCH

SLIDE SWITCH

INDICATOR LAMP

AC SOCKET

KEYBOARD SWITCH

TIMER SWITCH

POWER TOOL SWITCH

SPECIFICATIONS



10(3)A	250VAC	T125/55	5E4
16(4)A	250VAC	T125/55	
10(8)A	250VAC	T125/55	
10A	250VAC	T125	
16A	125VAC		
10.1A	250VAC	T125	
20A	125VAC		
1/2HP	250VAC	T125	
1/4HP	125VAC		

FEATURES

- Usage: General purpose
用途：通用
- Large size design with waterproof cap option
大尺寸設計，帶防水帽選項
- Single Pole, Double Pole option, Separation plate
單極、雙極選項，帶隔板
- Wide range function / Indicator function option
廣範功能/指示燈功能選項
- Temperature Rating: -10°C~85°C
額定溫度：-10°C~85°C
- Flammability Rating: UL94V-2 / Optional UL94V-0
可燃性等級：UL94V-2 / 可選 UL94V-0

ORDER INFORMATION

A	1	G	T	1	BK	BK	1	0	0	0	
FUNCTION	NO. OF POLES	CURRENT	TERMINAL TYPE	BASE TYPE	BASE COLOR	BUTTON COLOR	BUTTON TYPE	PRINTING	COLOR OF PRINTING	LAMP VOLTAGE	INTERNAL USE ONLY
A ON-OFF	1 Single	G 16(4)A 250VAC	T	1	BK Black	BK Black	1	0 NONE	0 None	0 None	
B ON-ON	2 Double	10(3)A 250VAC 5E4	T1		WT White	WT White	2	1	1 White	1 12V	
C ON-OFF-ON		20A 125VAC (Except function I)	T2		GE Grey	GE Grey	4	2	2 Black	2 24V	
D (ON)-OFF		H 16(4)A 250VAC	Q		RE Red	RE Red	I	3	3 Red	3 110V	
E ON-(OFF)		10(3)A 250VAC 5E4	S		GR Green	GR Green		4	4 Blue	4 220V	
F ON-(ON)		16A 125VAC	P		BL Blue	BL Blue		5	5 Yellow		
M ON-OFF-(ON)		1/2HP 250VAC			OR Amber	OR Amber		6			
X (ON)-OFF-(ON)		1/4HP 125VAC (For A, B, N functions only)			YE Yellow	YE Yellow		7			
N ON-OFF w/lamp								8			
I Indicator								9			

*For this option, please call factory for details

SUGGESTED PANEL HOLE SIZE

Panel thickness	x
1.0 ~ 1.5	29.0
1.5 ~ 2.0	29.4
2.0 ~ 3.0	29.8

