

# SB-31

## PUSH SWITCH SB-31 SERIES



SB-31A

SB-31D

SB-31D

### SPECIFICATIONS



3A	250VAC	T85	
6(3)A	250VAC	T85	5E4
10(3)A	250VAC	T85	
13(3)A	250VAC	T85	
16(6)A	250VAC	T85	
16A GP	125VAC	T105	
16A GP	125VAC	T85	5E4 (Except CQC and KC)
3A GP	250VAC	T105	
6A GP	125VAC	T105	
6(3)A	125/250VAC	T85	5E4
10(3)A	125/250VAC	T85	
16(6)A	125/250VAC	T85	
16A GP	125VAC	T105	
16A GP	125VAC	T85	5E4
3A	250VAC	T105	
6A	125VAC		
7.5A	250VAC	T105	
15A	125VAC		

RECOGNIZED COMPONENT



Conforms to UL STD.61058-1.  
Certified To CSA STD. C22.2 No. 61058-1.



### FEATURES

- Usage: **haircare, lighting device, robot, ironer**  
用途：美髮產品、照明設備、機器人、熨燙機
- **Small button design**  
小按鍵設計
- **Single Pole**  
單極
- **Temperature Rating: -10°C~105°C**  
額定溫度：-10°C~105°C
- **Flammability Rating: UL94V-2 / Optional UL94V-0**  
可燃性等級：UL94V-2 / 可選 UL94V-0

### ORDER INFORMATION

A	S	BK	BK	1	S	INTERNAL USE ONLY
FUNCTION	CURRENT	BASE COLOR	KNOB COLOR	KNOB TYPE	TERMINAL TYPE	
<b>A ON-OFF w/lock</b>	<b>S 3A 250VAC</b>	<b>BK Black</b>	<b>BK Black</b>	<b>1</b>	<b>S</b>	<b>P3</b>
<b>D (ON)-OFF</b>	<b>6A 125VAC</b>	<b>WT White</b>	<b>WT White</b>	<b>2</b>		<b>Q1</b>
<b>E ON-(OFF)</b>	<b>6(3)A 250VAC 5E4</b>			<b>3</b>	<b>S1</b>	
<b>ON-(OFF) w/sound</b>	<b>16(6)A 250VAC</b>				<b>P1</b>	
<b>G OFF-ON w/lock</b>	<b>16A GP 125VAC</b>				<b>P2</b>	
	<b>H2 10(3)A 250VAC</b>					
	<b>6(3)A 250VAC 5E4</b>					
	<b>16(6)A 250VAC</b>					
	<b>16A GP 125VAC 5E4</b>					

