

SR-68-2

ROCKER SWITCH SR-68-2 SERIES

ROCKER SWITCH



ROTARY SWITCH

PUSH SWITCH

MICRO SWITCH

SLIDE SWITCH

INDICATOR LAMP

AC SOCKET

KEYBOARD SWITCH

TIMER SWITCH

POWER TOOL SWITCH

SPECIFICATIONS



10(2)A 250VAC T85/55 5E4

16(3)A 250VAC T85/55

RECOGNIZED COMPONENT



Conforms to IUL STD 61058-1
Certified To CSA STD.C22.2
No. 61058-1.

16(3)A 125/250VAC T85



10.1A 250VAC T85

16A 125VAC

FEATURES

- Usage: Haircare
用途：美髮產品
- Single Pole
單極
- With circuit option design
帶電路選項設計
- Temperature Rating: -10°C~85°C
額定溫度：-10°C~85°C
- Flammability Rating: UL94V-2 / Optional UL94V-0
可燃性等級：UL94V-2 / 可選 UL94V-0

ORDER INFORMATION

A	L	BK	BK	0	0	0	1	INTERNAL USE ONLY
FUNCTION	CURRENT	BASE COLOR	BUTTON COLOR	BUTTON TYPE	PRINTING	COLOR OF PRINTING	BASE TYPE	
A OFF-ON₁₊₂	L 16(3)A 250VAC	BK Black	BK Black	0 NONE	0 NONE	0 None	1	
C ON₁-OFF-ON₂	16A 125VAC <small>(For A,C,K,W functions only)</small>		WT White	1	1	1 White	2	
K OFF-ON₁-ON₁₊₂			GE Grey	2	2	2 Black	3	
W ON₁-ON₂-ON₁₊₂	L 16(3)A 250VAC <small>(For M,X,Q,T,U,V functions only)</small>		RE Red	3	3	3 Red	4	
M ON₁-OFF-(ON₂)			GR Green	4	4	4 Blue	5	
X (ON₁)-OFF-(ON₂)	H 16(3)A 250VAC		BL Blue	5	5	5 Yellow	6	
Q OFF-ON₁-(ON₁₊₂)	10(2)A 250VAC 5E4		OR Amber	6	6	6 Silver		
T (ON₁)-ON₂-ON₁₊₂	16A 125VAC		YE Yellow	7	7			
U ON₁-ON₂-(ON₁₊₂)				8	8			
V (ON₁)-ON₂-(ON₁₊₂)				9	9			
				10	10			
				12	12			
				B	B			