

# ST-703

# ROTARY SWITCH ST-703 SERIES



ST-703

## SPECIFICATIONS

	6(5)A	250VAC	T85
	2.5A	250VAC	T85
	0.35A	125VDC	T85
<p>RECOGNIZED COMPONENT Conforms to UL STD. 61058-1. Certified To CSA STD. C22.2 No. 61058-1.</p>	6(5)A	125/250VAC	T85
	13A GP	125VAC	

## FEATURES

- Usage: Food processor, Washing machine, Coffee Machine, Oven, Audio  
用途：食品處理器、洗衣機、咖啡機、烤箱、音響
- Max 12 positions with specified circuit  
具有特定電路選項·最多 12 個檔位
- Screw nut / Wing Plate hold fixing  
螺絲螺母/翼仔板夾固定
- Temperature Rating: -10°C~125°C  
額定溫度：-10°C~125°C
- Flammability Rating: UL94V-2 / Optional UL94V-0  
可燃性等級：UL94V-2 / 可選 UL94V-0

## ORDER INFORMATION

<p><b>12</b></p> <p><b>CIRCUIT</b></p> <p>12 13 14 15 16 17 18 19 110 111 112</p> <p><b>R2 R3</b></p> <p>R3 R4 R5 R6 R7 R8</p> <p><b>L2 L3</b></p> <p>L3 L4 L5 L6 L7 L8</p>	<p><b>S</b></p> <p><b>CURRENT</b></p> <p>S 2.5A 250VAC</p> <p>0.35A 125VDC</p> <p>M 6(5)A 250VAC</p> <p>13A GP 125VAC</p>	<p><b>1</b></p> <p><b>HOUSING TYPE</b></p> <p>1</p> <p>2</p>	<p><b>1</b></p> <p><b>HANDLE TYPE</b></p> <p>1</p> <p>2</p> <p>3</p>	<p><b>S</b></p> <p><b>TERMINAL TYPE</b></p> <p>S</p> <p>P</p>	<p><b>BK</b></p> <p><b>BASE COLOR</b></p> <p><b>INTERNAL USE ONLY</b></p> <p>BK Black</p>
---	---	--	--	---	---

30° Rotary Angles

Top View: Ø29.5, 22.0  
Side View: 15.5, 11.5, 5.7, 0.50, 3.2, 4.95, 5.6  
Front View: 4.95, 06.0, 7.0

**SUGGESTED PANEL HOLE SIZE**

22.00  
thickness 2.00

**Wiring Diagram**