

SM-31

MICRO SWITCH SM-31 SERIES



SM-31D



SM-31E



SM-31F



SM-31F



SM-31F

SPECIFICATIONS



*UL 1054 approved



*UL 61058-1 approved

3(1)A	250VAC	T125	
3(3)A	250VAC	T85	5E4
8(2)A	250VAC	T125	
3A	250VAC	T125	
6A	125VAC		
8A	250VAC	T125	
15A	125VAC		
1/3HP	250VAC	T125	
1/6HP	125VAC		
6A GP	125VAC	T120	
11A GP	125VAC	T120	
8(2)A	125/250VAC	T120	
3(3)A	125/250VAC	T85	5E4
3(1)A	125/250VAC	T120	

FEATURES

- Usage: Food processor, Hair care, Electrical Curtain, Coffee machine
用途：食品處理器、美髮產品、電動窗簾、咖啡機
- With lever & special button option
帶槓桿和特殊按鈕選項
- Widely use in many area
廣泛應用領域
- Temperature Rating: -10°C~125°C
額定溫度：-40°C~125°C
- Flammability Rating: UL94V-2 / Optional UL94V-0
可燃性等級：UL94V-2 / 可選 UL94V-0

ORDER INFORMATION

D	S	BK	S	O
FUNCTION	CURRENT	BASE COLOR	TERMINAL TYPE	LEVER / KNOB TYPE
D (ON-OFF)	S 3(1)A 250VAC	BK Black	S	0
E ON-(OFF)	3(3)A 250VAC 5E4		H1	A
F ON-(ON)	6A 125VAC		S1	1
	H 8(2)A 250VAC		S5	2
	3(3)A 250VAC 5E4		P	3
	15A 125VAC		S5	4
	1/3HP 250VAC		H	5
	1/6HP 125VAC		P1	6
				7
				8
				9
				10
				14

INTERNAL USE ONLY

* For more lever options, please contact us

ROCKER SWITCH

ROTARY SWITCH

PUSH SWITCH

MICRO SWITCH

SLIDE SWITCH

INDICATOR LAMP

AC SOCKET

KEYBOARD SWITCH

TIMER SWITCH

POWER SWITCH