

# SR-98

## ROCKER SWITCH SR-98 SERIES



SR-98A



SR-98A



SR-98A



SR-98N



SR-98N



SR-98N

ROCKER SWITCH

ROTARY SWITCH

PUSH SWITCH

MICRO SWITCH

SLIDE SWITCH

INDICATOR LAMP

AC SOCKET

KEYBOARD SWITCH

TIMER SWITCH

POWER TOOL SWITCH

### SPECIFICATIONS

	6(2)A	250VAC	T125/55	5E4
	10(3)A	250VAC	T125/55	
 E199326	10.1A	250VAC	T125	
	16A	125VAC		
RECOGNIZED COMPONENT  Intertek 4006154 5022251 Conforms to UL STD. 61058-1. Certified To CSA STD. C22.2 No. 61058-1.	16A GP	125VAC	T85	
	6(2)A	125/250VAC	T125/55	5E4
	10(3)A	125/250VAC	T125/55	

### FEATURES

- Usage: Coffee machine  
用途：咖啡機
- Single Pole  
單極
- Round Button/With Indicator lamp option  
圓形按鈕//指示燈功能
- Temperature Rating: -10°C~125°C  
額定溫度：-10°C~125°C
- Flammability Rating: UL94V-2 / Optional UL94V-0  
可燃性等級：UL94V-2 / 可選 UL94V-0

### ORDER INFORMATION

A	H	Q	BK	BK	1	0	0	00	0	
FUNCTION	CURRENT	TERMINAL TYPE	BASE COLOR	BUTTON COLOR	BUTTON TYPE	PRINTING	COLOR OF PRINTING	SMALL LEN COLOR	LAMP VOLTAGE	INTERNAL USE ONLY
<b>A ON-OFF</b>	<b>H 10(3)A 250VAC</b>	<b>Q</b>	<b>BK Black</b>	<b>BK Black</b>	<b>1</b>	<b>0 NONE</b>	<b>0 None</b>	<b>00 None</b>	<b>0 None</b>	
<b>N ON-OFF w/lamp (Unswitched neutral)</b>	<b>6(2)A 250VAC 5E4</b> <b>16A 125VAC</b>	<b>S</b>	<b>WT White</b>	<b>GE Grey</b>	<b>2</b>	<b>1</b>	<b>1 White</b>	<b>RE Red</b>	<b>3 110V</b>	
		<b>Q1</b>	<b>RE Red</b>	<b>RE Red</b>	<b>3</b>	<b>2</b>	<b>2 Black</b>	<b>GR Green</b>	<b>4 220V</b>	
		<b>Q2</b>	<b>GR Green</b>	<b>GR Green</b>	<b>4</b>	<b>3</b>	<b>3 Red</b>	<b>BL Blue</b>		
		<b>Q3</b>	<b>BL Blue</b>	<b>BL Blue</b>	<b>5</b>	<b>8</b>	<b>4 Blue</b>	<b>OR Amber</b>		
		<b>A</b>	<b>OR Amber</b>	<b>OR Amber</b>	<b>12</b>	<b>9</b>	<b>5 Yellow</b>			
		<b>B</b>	<b>YE Yellow</b>	<b>YE Yellow</b>	<b>R</b>	<b>A</b>				

### SUGGESTED PANEL HOLE SIZE

