

SM-51

MICRO SWITCH SM-51 SERIES

ROCKER SWITCH



SM-51D



SM-51D



SM-51E



SM-51F



SM-51F

ROTARY SWITCH

PUSH SWITCH

MICRO SWITCH

SLIDE SWITCH

INDICATOR LAMP

AC SOCKET

KEYBOARD SWITCH

TIMER SWITCH

POWER SWITCH

SPECIFICATIONS



(≥ 3mm contact gap available on request)



*UL 1054 approved



*UL 61058-1 approved

15A	250VAC	T125
16(4)A	250VAC	T125

10.1A	250VAC	
20A	125VAC	T125
10.1A	250VAC	
16A	125VAC	T125

15A	125/250VAC	T125
16A GP	125VAC	T125
20A GP	125VAC	T125
10(3)A	125/250VAC	T125 5E4
16(4)A	125/250VAC	T125
3/4 HP	125/250VAC	T125 6E3
1/2 HP	125/250VAC	T125 6E3

FEATURES

- Usage: Food processor, Hair care, Cleaning Robot, Coffee machine
用途：食品處理器、美髮產品、清潔機器人、咖啡機
- With lever & special button option
帶槓桿和特殊按鈕選項
- Horizontal terminal
橫向端子
- Temperature Rating: -10°C~125°C
額定溫度：-10°C~125°C
- Flammability Rating: UL94V-2 / Optional UL94V-0
可燃性等級：UL94V-2 / 可選 UL94V-0

ORDER INFORMATION

D	H	BK	Q	N	O
FUNCTION	CURRENT	BASE COLOR	TERMINAL TYPE	LEVER POSITION	LEVER / SPECIAL KNOB TYPE
D (ON)-OFF	H 16(4)A 250VAC	BK Black	Q	N	O
E ON-(OFF)	16A 125VAC		Q2	No Lever	A
F ON-(ON)	L 16(4)A 250VAC		Q1	Standard ratio	C
	20A 125VAC		T	High ratio	1, 2, 3, 4, 5, 6

INTERNAL USE ONLY

For more lever options, please see next page

