

SR-03

ROCKER SWITCH SR-03 SERIES



SR-03A



SR-03A



SR-03P



SR-03P



SR-03P

ROCKER SWITCH

PUSH SWITCH

PUSH SWITCH

MICRO SWITCH

SLIDE SWITCH

INDICATOR LAMP

AC SOCKET

KEYBOARD SWITCH

TIMER SWITCH

POWER TOOL SWITCH

SPECIFICATIONS

	6(4)A 250VAC T85	T105/55	5E4
	10(8)A 250VAC T85	T105/55	
	10A 250VAC T105		
	16A 125VAC		
	1/2HP 250VAC T105		
	1/4HP 125VAC		
<p>Conforms to UL STD.61058-1. Certified To CSA STD.C22.2 No. 61058-1.</p>	10(8)A 250VAC T105/55	1E4 μ	
	6(4)A 250VAC T85	5E4 μ	
	16AGP 125VAC T105/55	1E4 μ	
	10AGP 250VAC T105/55	1E4 μ	

FEATURES

- Usage: General purpose
用途：通用
- Lamp with switch neutral design
帶燈串聯設計
- Single Pole
單極
- ON-OFF function
開關功能
- Temperature Rating: -10°C~85°C
額定溫度：-10°C~85°C
- Flammability Rating: UL94V-2 / Optional UL94V-0
可燃性等級：UL94V-2 / 可選 UL94V-0

ORDER INFORMATION

A	H	Q	BK	BK	2	0	0	0	
FUNCTION	CURRENT	TERMINAL TYPE	BASE COLOR	BUTTON COLOR	BUTTON TYPE	PRINTING	COLOR OF PRINTING	LAMP VOLTAGE	INTERNAL USE ONLY
A ON-OFF	H 10(8)A 250VAC	Q	BK Black	BK Black	2	0 NONE	0 None	0 None	
P ON-OFF w/lamp (switched neutral)	6(4)A 250VAC 5E4	P7	WT White	WT White		1	1 White	3 110V	
	16A 125VAC	Q1	GE Grey	GE Grey		2	2 Black	4 220V	
	1/2HP 250VAC	Q2	RE Red	RE Red		3	3 Red		
	1/4HP 125VAC	P8	GR Green	GR Green		4	4 Blue		
		P9	BL Blue	BL Blue		5	5 Yellow		
		S	OR Amber	OR Amber		8			
		S1	YE Yellow	YE Yellow		9			
		P1				A			
		P2				B			
		P3							
		P6							

SUGGESTED PANEL HOLE SIZE

Panel thickness	x
0.75 ~ 1.25	19.2
1.25 ~ 2.0	19.4
2.0 ~ 3.0	19.6