

SB-17

PUSH SWITCH SB-17 SERIES



SB-17E

SPECIFICATIONS



1A	250VAC	T85
2A	125VAC	

FEATURES


- Usage: toy, emergency light, Small power & signal usage
用途：玩具和應急燈·低功率及信號使用
- Single Pole with separated plate
單極·帶隔板
- Temperature Rating: -10°C~85°C
額定溫度：-10°C~85°C
- Flammability Rating: UL94V-2 / Optional UL94V-0
可燃性等級：UL94V-2 / 可選 UL94V-0

ORDER INFORMATION






D	BK	BK	Q	1	0	0		
FUNCTION	BASE COLOR	KNOB COLOR	TERMINAL TYPE	BASE TYPE	PRINTING	COLOR OF PRINTING	INTERNAL USE ONLY	
D (ON)-OFF	BK Black	BK Black	Q	1	0 NONE	0 None		
E ON-(OFF)	WT White	WT White			1	1 White		
	GE Grey	GE Grey			2	2 Black		
	RE Red	RE Red				3 Red		
	GR Green	GR Green				4 Blue		
	BL Blue	BL Blue				5 Yellow		
	OR Amber	OR Amber						
	YE Yellow	YE Yellow						

SUGGESTED PANEL HOLE SIZE

Panel thickness	x
0.75 ~ 1.25	12.8
1.25 ~ 2.0	13.0
2.0 ~ 3.0	13.2



WIRING DIAGRAM



ROCKER SWITCH

ROTARY SWITCH

PUSH SWITCH

MICRO SWITCH

SLIDE SWITCH

INDICATOR LAMP

AC SOCKET

KEYBOARD SWITCH

TIMER SWITCH

POWER TOOL SWITCH