

SL-101

SLIDE SWITCH SL-101 SERIES



SL-101



SL-101



SL-101



SL-101



SL-101



SL-101

ROCKER SWITCH

ROTARY SWITCH

PUSH SWITCH

MICRO SWITCH

INDICATOR LAMP

AC SOCKET

KEYBOARD SWITCH

TIMER SWITCH

POWER TOOL SWITCH

SPECIFICATIONS



(For KEMA, ENEC, CQC approved only)



E199326

RECOGNIZED COMPONENT



Intertek 4036154

Conforms to UL STD.61058-1.
Certified To CSA STD.C22.2
No. 61058-1.

8(3)A	250VAC	T125
10(2)A	250VAC	T85
12(2)A	250VAC	T85
6.5A	250VAC	T125
13A	125VAC	
8A	250VAC	T125
16A	125VAC	
8(3)A	250VAC	T85
10(2)A	250VAC	T85
12(2)A	250VAC	T85
8A GP	250VAC	T85
16A GP	125VAC	T85

FEATURES

- Usage: Haircare product
用途：美髮產品
- Circuit: 1P2T-2P5T
電路：1P2T-2P5T
- Different Knob option
不同的旋鈕選項
- Temperature Rating: -10°C~125°C
額定溫度：-10°C~125°C
- Flammability Rating: UL94V-2 / Optional UL94V-0
可燃性等級：UL94V-2 / 可選 UL94V-0

ORDER INFORMATION

11	11	L	1	S
CIRCUIT	REF: BASE DIMENSION	CURRENT	KNOB TYPE	TERMINAL TYPE
11 1P1T	11	L 8(3)A 250VAC 10(2)A 250VAC 16A GP 125VAC		
21 2P1T	21			
12 1P2T	12			
22 2P2T	12			
13 1P3T	13			
23 2P3T	13			
14 1P4T	14			
24 2P4T	14			
15 1P5T	15			
25 2P5T	15			
	14			
	24			
	15			
	25			

* Extension of knob wings available