

# SL-308

## SLIDE SWITCH SL-308 SERIES



SL-308-S1



SL-308-P

### SPECIFICATIONS



8(2)A 250VAC T85

10A GP 250VAC T85

5(2)A 250VAC T85

RECOGNIZED COMPONENT



Conforms to UL STD. 61058-1.  
Certified To CSA STD. C22.2  
No. 61058-1.

5A GP 250VAC T85

10A GP 125VAC T85

### FEATURES

- Usage: Haircare product, High Speed Hair Dryer  
用途：美髮產品·高速吹風機
- 2 terminals output, safe breaking design  
2端子輸出·安全斷路設計
- 3 Positions  
3個檔位
- Temperature Rating: -10°C~85°C  
額定溫度：-10°C~85°C
- Flammability Rating: UL94V-2 / Optional UL94V-0  
可燃性等級：UL94V-2 / 可選 UL94V-0

### ORDER INFORMATION

<b>001</b>	<b>M</b>	<b>1</b>	<b>S1</b>	INTERNAL USE ONLY
<b>CIRCUIT</b>	<b>CURRENT</b>	<b>NOB TYPE</b>	<b>TERMINAL TYPE</b>	
001	M 5(2)A 250VAC	1	S1	
MORE	10A GP 125VAC			

### CIRCUIT OPTIONS

\*CIRCUIT001

POSITION	ELECTRIC CIRCUIT	
	C-1	C-2
1		
2	•	
3	•	•

\*with production mould  
For more circuit options, please call factory

### CIRCUIT DIAGRAM

