

SB-35

PUSH SWITCH SB-35 SERIES



SB-35A

SPECIFICATIONS

	10(4)A	250VAC	T85	
	6(3)A	250VAC	T85	5E4
	6(3)A	250VAC	T85	5E4
	10(4)A	250VAC	T85	
*UL 61058-1 approved	16A GP	125/250VAC	T85	





FEATURES

- Usage: haircare, general usage
用途：美髮產品和一般用途
- Single Pole
單極
- Small button design
小按鍵設計
- Wing fixing housing design option
機翼固定外殼設計選項
- Temperature Rating: -10°C~85°C
額定溫度：-10°C~85°C
- Flammability Rating: UL94V-2 / Optional UL94V-0
可燃性等級：UL94V-2 / 可選 UL94V-0


ORDER INFORMATION

A	H	BK	BK	1	1	S	
FUNCTION	CURRENT	HOUSING COLOR	KNOB COLOR	HOUSING TYPE	KNOB TYPE	TERMINAL TYPE	INTERNAL USE ONLY
A ON-OFF w/lock	H 10(4)A 250VAC	BK Black	BK Black	1	1	S	
B ON-ON w/lock	6(3)A 250VAC 5E4			2			
D (ON)-OFF	16A GP 125/250VAC						
E ON-(OFF)							
F ON-(ON)							

HOUSING 1 SUGGESTED PANEL HOLE SIZE



CIRCUIT DIAGRAM



ROCKER SWITCH

ROTARY SWITCH

PUSH SWITCH

MICRO SWITCH

SLIDE SWITCH

INDICATOR LAMP

AC SOCKET

KEYBOARD SWITCH

TIMER SWITCH

POWER TOOL SWITCH